



FEATURES & BENEFITS

- + **Precise Temperature Control** - Electronic temperature control with LED digital display - set temperature anywhere between 41-64°F and the wine cooler will hold it precisely
- + **Maximum Storage Capacity** - Holds up to 162 bottles for maximum storage
- + **Dual Temperature Zones** - Store red, white, and sparkling beverages at the appropriate temperature for proper preservation and maximum taste
- + **Full-extension Racks** - Full-extension smooth-glide wine racks allows for easy access to your prized vintage collection - the wood front give the metal racks a sleek, high-end design
- + **Interior Lights** - LED illuminating lighting has three unique color selections to complement the ambiance of the room
- + **Security lock** - Security lock to keep out unwanted guests
- + **Sabbath Mode** - While in Sabbath mode, the wine cooler will disable the lights, while normal cooling operations will still take place
- + **Door Alarm** - Door alarm notifies you if the door is left ajar for too long
- + **Charcoal Filtration System** - An active charcoal filtration system to ensures air purity, cooling efficiency and helps to maintain an odor free cabinet for the storage of your wine.

Product: 24 Inch Dual Zone Wine Cooler

Model Number: TWC2403DI

PRODUCT DIMENSIONS

Cooler Width (in.)	23 15/16"
Depth (Excluding Handles) (in.)	27
Depth (Including Handles) (in.)	29 1/4"
Depth (Less Door) (in.)	24 13/16"
Depth With Door Open 90 Degrees (in.)	49 5/8"
Height to Top of Door Hinge (in.)	74
Product Depth (in.)	27
Product Height (in.)	73 5/8"
Product Width (in.)	23 7/8"

TECHNICAL DETAILS

Bottle Storage Capacity	162
Color/Finish	Stainless Steel
Voltage (Volts)	120
Minimum Temperature (F)	41
Number of Doors	1 Door
Number of Refrigerator Shelves	13 Shelves
Number of Temperature Zones	Double Zone
Operational Features	Sabbath Mode
Product Weight (lb.)	262 lb

WARRANTY: TWO YEAR LIMITED WARRANTY



TWC2403DI Installation

This unit is designed for both built-in or free-standing installation. If you plan to use this unit in a built-in application, please follow the requirements shown below.

Cut-out Dimension	
Width	≥24 1/8"
Depth	≥27 5/8"
Height	≥74"

