



**Product:** 30 Inch Professional Gas Range in Stainless Steel  
**Model Number:** HRG3080U / HRG3080ULP

### TECHNICAL DETAILS

Fuel Type	Natural Gas / LP Convertible
Electrical Requirements	120V
Circuit Breaker (A)	15 or 20 A
Frequency (Hz)	60 Hz

### BURNER PERFORMANCE

Total Burners	4
(1) Front Left (Single)	18,000 BTU
(2) Front Right (Dual Burner with simmer function)	15,000 BTU (650 BTU for Simmer)
(3) Rear Left (Single)	12,000 BTU
(4) Rear Right (Single)	12,000 BTU
Tube Broil burner	13,000 BTU
U-shape Bake burner	22,000 BTU



### FEATURES & BENEFITS

- High-Powered BTU Burners** - From a high-powered 18,000 BTU burner to a burner with a steady 650 BTU simmer function, this range gives you the power you need for large family meals and the consistent low heat desired for cooking delicate sauces or melting chocolate
- LuxGlide™ Telescopic Racks** - Telescopic racks use ball bearing rack guides for an effortless glide in and out of the oven. This luxury feature allows the rack to extend fully without tipping over for smooth, easy handling of even the heaviest dishes, and adjusts to fit different rack support levels
- Gas Flame Broiler** - Reflective gas flame broiler radiates heat evenly to sear your food and seal in the juices
- Commercial Convection Fan** - Convection fan provides controlled heat distribution for fast and efficient cooking
- LED Control Panel Lights** - When in operation, the LED control panel lights illuminate a striking blue for an added pop of color
- Large Oven Capacity** - 4.2 cu. ft. oven capacity can accommodate multiple dishes for enhanced cooking
- Continuous Cast-Iron Cooking Grates** - Heavy-duty continuous cast-iron cooking grates that can handle any size cookware
- Brilliant Blue Porcelain Interior** - The brilliant blue porcelain interior adds a bold, stylish touch to your professional range
- Heavy Duty Control Knobs** - Heavy duty, die-cast metal burner control knobs add style and durability
- Black Porcelain Spill Tray** - Black porcelain spill tray on cooktop catches the mess and makes cleanup easy
- Automatic Reignition Feature** - Automatic reignition feature relights an extinguished flame for safer cooking

### ACCESSORIES (NOT INCLUDED)

Liquid Propane Gas Conversion Kit	LPKHRG3080U
30-inch Telescopic Rack	TR30SS
30-inch Island Trim	ITHRG3080U
Cast Iron Reversible Griddle	RG1022
Wok Ring	WK01
Cast Iron Range Griddle	RG1032

**LIMITED WARRANTY: 24 MONTHS ON PARTS AND LABOR**



### PRODUCT DIMENSIONS



Product Width	30"
Product height (from bottom to top of back splash)	38 3/8" - 39 3/8"
Product height (from bottom to top of side panel)	35 9/16" - 36 9/16"
Product depth (from back panel to bullnose)	27 15/16"
Product depth (from back panel to control board)	26 9/16"
Product depth (from back panel to side panel front)	24 13/16"
Depth of control panel (minimum)	1 11/16"
Depth of control panel (bullnose)	3 1/8"
Cast iron cooking grate (W x L)	10 3/4" x 23"

### REQUIRED CUTOUT SIZE

30 1/8" x 24 13/16" x 35 9/16" (+1")

### OVEN DIMENSIONS

Oven Cavity Dimension	24"W x 15 1/4"H x 18"D
Oven Rack Dimension	22 3/4" x 15 1/2"
Distance Between Oven Rack	2 1/8"



NG: Input Pressure: 7 inches, Output Pressure: 5 inches  
LP: Input Pressure: 11 inches Output Pressure: 10 inches  
Size of Regulator: 1/2 inch

